

Prokol Cleaner 605-L

Description and application

Prokol Cleaner 605-L is a powerful, water soluble and safe solvent that is biodegradable and alkalinely designed for fast and efficient removal of grease, dirt, carbon, oil, soot, nicotine stains and other persistent stains for numerous applications.

Prokol Cleaner 605-L is a universal cleaning and degreasing agent for treating coated and/or non-coated surfaces. Cleaner 605-L can be diluted with hot or cold water. For best results apply Cleaner 605-L with a spray bottle, then wipe the surface off immediately with a moist cloth. When cleaning machinery etc., rinse with water afterwards.

Article number and packaging

20521-1	1 litre spray bottle
20521-10	10 litre can

Properties

- Biodegradable
- Intensive cleaning

Liquid product properties

Colour	Clear
Density	1,02 kg /l
Shelf life	At least 12 months after the date of production, if stored cool in unopened packaging and protected against frost.

Application information

Dosage	Normal contamination: 1 litre Prokol Cleaner 605-L for 10 litres of water. Severe contamination: 1 litre Prokol Cleaner 605-L for 5 litres of water.
Special application	Prokol Cleaner 605-L can be applied in undiluted form when cleaning severe soot contamination, e.g. as a bilge cleaner for ships, etc
PH- Values at 20°C	1 part Cleaner 605-L : 2 parts water 12.8 1 part Cleaner 605-L : 5 parts water 12.5 1 part Cleaner 605-L : 10 parts water 12.2 1 part Cleaner 605-L : 20 parts water 11.8

Warning

Prokol Cleaner 605-L should not be used on glass or mirrors as it may damage the surface.

Safety information

Consult for the safety information the Safety Data Sheet.

Important

Projects and uses can vary greatly. Always contact your supplier if in doubt about a certain use, choice of material or surface treatment. All the technical information given in this technical information sheet is based on laboratory tests. Information can change, depending on the conditions.

Legal notification

The information and, in particular, the recommendations concerning the application and final use of Prokol products is issued in good faith based on Prokol's current knowledge and experience of products that are correctly stored, handled and applied under normal conditions.

In practice, the differences in materials, substrates and local conditions are such that no guarantee can be given concerning the marketability or suitability for a certain objective, nor can any liability arise from any legal relationship based on this information, nor from any written recommendations or other advice that is given. The property rights of third parties must be respected.

Prokol guarantees that its products are free from manufacturing faults. Multi-component products are a finished product once the components have been mixed and processed. When mixed and processed correctly, the product will achieve the specifications given. Prokol can only guarantee the product when surfaces are processed and pre-treated correctly.

All orders are accepted under the current sales and delivery conditions.

Users must always refer to the most recent product safety information sheet and product information sheet for the product concerned. A copy of these sheets will be provided on request and is also available from www.prokol.nl. This requires a login name and a password.

The publication of this product information sheet makes all previous product information sheets for this product invalid.



Tel. +31 (0)85 78 200 20 • Fax. +31 (0)85 78 200 21
www.prokol.nl • info@prokol.nl

Liquid synthetic materials for a sustainable future